

STREET/STRIP

PROCHARGER SUPERCHARGER SPECIFICATIONS



	A-1P	A-1R	B-1	CS-1	C-1	C-2	C-1R	P600B	P-1SC	P-1SC-1	P-1X	P-1SC-2	D-1	D-1SC	D-1X
VOLUTE DIAMETER	7"	7"	7"	7"	7"	7"	8"	9"	9"	9"	9"	9"	9"	9"	9"
MAX SUPERCHARGED HP	100	150	250	550	675	725	675	775	825	825	875	825	925	925	1000
MOTOR BASE HP RANGE*	25-75	50-95	60-150	150-325	150-325	175-375	150-325	200-500	200-500	200-450	300-500	200-450	300-500	300-500	300-550
MAX FLOW (CFM)	200	450	600	900	1,000	1,000	1,000	1,150	1,200	1,200	1,275	1,200	1,400	1,400	1,500
MAX BOOST (PSI)	15	15	20	24	24	24	30	24	30	32	32	30	32	32	32
INLET HOSE DIAMETER	3"	3"	3"	3.5"	3.5"	3.5"	4"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"
INDUCER DIAMETER	2.02"	2.28"	2.28"	2.66"	2.75"	3.14"	2.83"	3.37"	3.37"	3.37"	3.57"	3.24"	3.37"	3.37"	3.57"
EXDUCER DIAMETER	4"	3.2"	3.2"	3.7"	4.25"	4.25"	3.89"	6.25"	6.25"	5.25"	5.56"	6"	6.25"	6.25"	6.20"
OUTLET HOSE DIAMETER	2"	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"
OUTLET I.D.	1.75"	1.75"	1.75"	2.12"	2.12"	2.12"	2.60"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"
MAX IMPELLER RPM	75,000	75,000	110,000	80,000	80,000	80,000	110,000	60,000	62,000	65,000	65,000	60,000	65,000	62,000	62,000
INTERNAL STEP-UP	4.11:1	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes
OIL CAPACITY	2.5 oz	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz

BOLT ON 50-85% MORE POWER ON PUMP GAS WITH INTERCOOLED PROCHARGER KITS

See Other Side for F-Series Supercharger Specs

