

# RACE

## PROCHARGER SUPERCHARGER SPECIFICATIONS



	F-1C	F-1R	F-1X	F-2	F-3D-102	F-3D-106	F-3R-102	F-1X-12 F-3R-112	F-3R-121	F-3R-130	F-3R-136	F-3R-140	F-3X-140	F-4X-140	F-4X-142
<b>VOLUTE DIAMETER</b>	9.75"	9.75"	10.5"	10.5"	10.5"	10.5"	12"	12"	12"	12"	12"	12"	13.5"	13.5"	13.5"
<b>MAX SUPERCHARGED HP</b>	1,100	1,250	1,400	1,450	1,500	1,800	1,600	2,100	2,400	2,700	3,000	3,400	3,500	3,500	3,700
<b>MOTOR BASE HP RANGE</b>	300-550	375-550	375-550	425-600	550-750	550-750	375-550	CALL	CALL	CALL	CALL	CALL	CALL	CALL	CALL
<b>MAX FLOW (CFM)</b>	1,625	1,700	2,000	2,700	1,900	2,200	2,000	2,300	3,100	3,600	4,000	4,400	4,500	4,500	TBD
<b>MAX BOOST (PSI)</b>	38	38	38	38	38	38	38	38	40	45	50	58	60	60	TBD
<b>INLET HOSE DIAMETER</b>	4"	4.05"	4.8"	4.6"	4.8"	4.8"	6"	5"	5.5"	5.75"	5.75"	5.75"	6"	6"	6"
<b>INDUCER DIAMETER</b>	3.7"	4"	4.20"	4.5"	4"	4.2"	4"	4.4"	4.8"	5.12"	5.35"	5.47"	5.47"	5.47"	TBD
<b>EXDUCER DIAMETER</b>	5.56"	6"	6"	6.75"	6"	6"	6.75"	6.75"	6.75"	7.22"	7.22"	7.22"	7.22"	7.22"	7.50"
<b>OUTLET HOSE DIAMETER</b>	3"	3"	3.5"	3.5"	3.5"	3.5"	4"	4"	4"	4"	4"	4"	4.5"	4.5"	4.5"
<b>OUTLET I.D.</b>	2.62"	2.62"	3.15"	3.15"	3.15"	3.15"	3.59"	3.59"	3.59"	3.59"	3.59"	3.59"	4"	4"	4"
<b>MAX IMPELLER RPM</b>	74,000	68,000	72,000	65,000	74,000	74,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000
<b>INTERNAL STEP-UP</b>	5.40:1	5.40:1	5.40:1	5.40:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	4.77:1	4.77:1
<b>REVERSE ROTATION OPTION</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No
<b>SELF CONTAINED</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>OIL CAPACITY</b>	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	6 oz	6 oz	6 oz	6 oz

5" V-band flange discharge option available for 12"-13.5" head units

See Other Side for Street Supercharger Specs

INVENTED, ENGINEERED, MADE IN THE USA

04/21

FIND YOUR BOOST AT  
**PROCHARGER.COM**

14801 W. 114th Terrace, Lenexa KS 66215 PH: (913) 338-2886 FX: (913) 338-2879



# STREET

## PROCHARGER SUPERCHARGER SPECIFICATIONS



	A-1R	B-1	CS-1	C-1	C-2	P600B	P-1SC	P-1SC-1	P-1X	P-1SC-2	D-1	D-1SC	D-1X	F-1D	F-1	F-1A	F-1A-91	F-1A-94	
<b>VOLUTE DIAMETER</b>	7"	7"	7"	7"	7"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
<b>MAX SUPERCHARGED HP</b>	150	250	550	675	725	775	825	825	950	825	925	925	1075	1050	1050	1100	1200	1300	
<b>MOTOR BASE HP RANGE*</b>	50-95	60-150	150-325	150-325	175-375	200-500	200-500	200-450	300-500	200-450	300-500	300-500	300-550	300-500	300-500	300-500	300-500	300-550	
<b>MAX FLOW (CFM)</b>	450	600	900	1000	1000	1150	1200	1200	1275	1200	1400	1400	1500	1500	1525	1575	1600	1625	
<b>MAX BOOST (PSI)</b>	15	20	24	24	24	24	30	32	32	30	32	32	32	34	38	38	38	38	
<b>INLET HOSE DIAMETER</b>	3"	3"	3.5"	3.5"	3.5"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	4"
<b>INDUCER DIAMETER</b>	2.28"	2.28"	2.66"	2.75"	3.14"	3.37"	3.37"	3.37"	3.57"	3.24"	3.37"	3.37"	3.57"	3.37"	3.57"	3.5"	3.57"	3.7"	
<b>EXDUCER DIAMETER</b>	3.2"	3.2"	3.7"	4.25"	4.25"	6.25"	6.25"	5.25"	5.56"	6"	6.25"	6.25"	6.20"	6.25"	6"	5.56"	5.56"	5.56"	
<b>OUTLET HOSE DIAMETER</b>	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	
<b>OUTLET I.D.</b>	1.75"	1.75"	2.12"	2.12"	2.12"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	
<b>MAX IMPELLER RPM</b>	75,000	11,000	80,000	80,000	80,000	60,000	62,000	65,000	65,000	60,000	65,000	62,000	62,000	65,000	70,000	74,000	74,000	74,000	
<b>INTERNAL STEP-UP</b>	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	
<b>REVERSE ROTATION OPTION</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
<b>SELF CONTAINED</b>	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
<b>OIL CAPACITY</b>	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz	4 oz	4 oz	4 oz	4 oz	4 oz	

See Other Side for F-Series Supercharger Specs

INVENTED, ENGINEERED, MADE IN THE USA

04/21

FIND YOUR BOOST AT  
**PROCHARGER.COM**

14801 W. 114th Terrace, Lenexa KS 66215 PH: (913) 338-2886 FX: (913) 338-2879

