

F-SERIES

PROCHARGER SUPERCHARGER SPECIFICATIONS



	F-1D	F-1	F-1A	F-1A-91	F-1A-94	F-1C	F-1R	F-1X	F-2	F-3D-102	F-3D-106	F-3R-102	F-1X-12 F-3R-112	F-3R-121	F-3R-130	F-3R-136	F-3R-140	F-3X-140
VOLUTE DIAMETER	9"	9"	9"	9"	9"	9.75"	9.75"	10.5"	10.5"	10.5"	10.5"	12"	12"	12"	12"	12"	12"	13.5"
MAX SUPERCHARGED HP	1,050	1,050	1,100	1,200	1,300	1,100	1,250	1,400	1,450	1,500	1,800	1,600	2,100	2,400	2,700	3,000	3,400	3,500
MOTOR BASE HP RANGE	300-500	300-500	300-500	300-500	300-500	300-550	375-550	375-550	425-600	375-550	375-550	375-550	375-550	500-580	600-900	700-1000	700-1000	700-1000
MAX FLOW (CFM)	1,500	1,525	1,575	1,600	1,625	1,625	1,700	2,000	2,700	1,900	2,200	2,000	2,300	3,100	3,600	4,000	4,400	4,500
MAX BOOST (PSI)	34	38	38	38	38	38	38	38	38	38	38	38	38	40	45	50	58	60
INLET HOSE DIAMETER	3.75"	3.75"	3.75"	3.75"	4"	4"	4.05"	4.8"	4.6"	4.8"	4.8"	5"	5"	5.5"	5.75"	5.75"	5.75"	6"
INDUCER DIAMETER	3.37"	3.57"	3.5"	3.57"	3.7"	3.7"	4"	4.20"	4.5"	4"	4.2"	4"	4.4"	4.8"	5.12"	5.35"	5.47"	5.47"
EXDUCER DIAMETER	6.25"	6"	5.56"	5.56"	5.56"	5.56"	6"	6"	6.75"	6"	6"	6.75"	6.75"	6.75"	7.22"	7.22"	7.22"	7.22"
OUTLET HOSE DIAMETER	3"	3"	3"	3"	3"	3"	3"	3.5"	3.5"	3.5"	3.5"	4"	4"	4"	4"	4"	4"	4.5"
OUTLET I.D.	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	3.15"	3.15"	3.15"	3.15"	3.59"	3.59"	3.59"	3.59"	3.59"	3.59"	4"
MAX IMPELLER RPM	65,000	70,000	74,000	74,000	74,000	74,000	68,000	72,000	65,000	74,000	74,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000
INTERNAL STEP-UP	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OIL CAPACITY	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz

5" V-band flange discharge option available for 12"-13.5" head units

See Other Side for Street Supercharger Specs

08/20

INVENTED, ENGINEERED, MADE IN THE USA



FIND YOUR BOOST AT
PROCHARGER.COM

14801 W. 114th Terrace, Lenexa KS 66215 PH: (913) 338-2886 FX: (913) 338-2879

