

STREET

PROCHARGER SUPERCHARGER SPECIFICATIONS



	A-1R	B-1	CS-1	C-1	C-2	P600B	P-1SC	P-1SC-1	P-1X	P-1SC-2	D-1	D-1SC	D-1X	F-1D	F-1	F-1A	F-1A-91	F-1A-94	
VOLUTE DIAMETER	7"	7"	7"	7"	7"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
MAX SUPERCHARGED HP	150	250	550	675	725	775	825	825	950	825	925	925	1075	1050	1050	1100	1200	1300	
MOTOR BASE HP RANGE*	50-95	60-150	150-325	150-325	175-375	200-500	200-500	200-450	300-500	200-450	300-500	300-500	300-550	300-500	300-500	300-500	300-500	300-550	
MAX FLOW (CFM)	450	600	900	1000	1000	1150	1200	1200	1275	1200	1400	1400	1500	1500	1525	1575	1600	1625	
MAX BOOST (PSI)	15	20	24	24	24	24	30	32	32	30	32	32	32	34	38	38	38	38	
INLET HOSE DIAMETER	3"	3"	3.5"	3.5"	3.5"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	4"
INDUCER DIAMETER	2.28"	2.28"	2.66"	2.75"	3.14"	3.37"	3.37"	3.37"	3.57"	3.24"	3.37"	3.37"	3.57"	3.37"	3.57"	3.5"	3.57"	3.7"	
EXDUCER DIAMETER	3.2"	3.2"	3.7"	4.25"	4.25"	6.25"	6.25"	5.25"	5.56"	6"	6.25"	6.25"	6.20"	6.25"	6"	5.56"	5.56"	5.56"	
OUTLET HOSE DIAMETER	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	
OUTLET I.D.	1.75"	1.75"	2.12"	2.12"	2.12"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	
MAX IMPELLER RPM	75,000	11,000	80,000	80,000	80,000	60,000	62,000	65,000	65,000	60,000	65,000	62,000	62,000	65,000	70,000	74,000	74,000	74,000	
INTERNAL STEP-UP	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1	5.40:1	5.40:1	5.40:1	5.40:1	5.40:1	
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
OIL CAPACITY	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz	4 oz	4 oz	4 oz	4 oz	4 oz	

See Other Side for F-Series Supercharger Specs

INVENTED, ENGINEERED, MADE IN THE USA

04/21

FIND YOUR BOOST AT
PROCHARGER.COM

14801 W. 114th Terrace, Lenexa KS 66215 PH: (913) 338-2886 FX: (913) 338-2879



RACE

PROCHARGER SUPERCHARGER SPECIFICATIONS



	F-1C	F-1R	F-1X	F-2	F-3D-102	F-3D-106	F-3R-102	F-1X-12 F-3R-112	F-3R-121	F-3R-130	F-3R-136	F-3R-140	F-3X-140	F-4X-140	F-4X-142
VOLUTE DIAMETER	9.75"	9.75"	10.5"	10.5"	10.5"	10.5"	12"	12"	12"	12"	12"	12"	13.5"	13.5"	13.5"
MAX SUPERCHARGED HP	1,100	1,250	1,400	1,450	1,500	1,800	1,600	2,100	2,400	2,700	3,000	3,400	3,500	3,500	3,700
MOTOR BASE HP RANGE	300-550	375-550	375-550	425-600	550-750	550-750	375-550	CALL	CALL	CALL	CALL	CALL	CALL	CALL	CALL
MAX FLOW (CFM)	1,625	1,700	2,000	2,700	1,900	2,200	2,000	2,300	3,100	3,600	4,000	4,400	4,500	4,500	TBD
MAX BOOST (PSI)	38	38	38	38	38	38	38	38	40	45	50	58	60	60	TBD
INLET HOSE DIAMETER	4"	4.05"	4.8"	4.6"	4.8"	4.8"	6"	5"	5.5"	5.75"	5.75"	5.75"	6"	6"	6"
INDUCER DIAMETER	3.7"	4"	4.20"	4.5"	4"	4.2"	4"	4.4"	4.8"	5.12"	5.35"	5.47"	5.47"	5.47"	TBD
EXDUCER DIAMETER	5.56"	6"	6"	6.75"	6"	6"	6.75"	6.75"	6.75"	7.22"	7.22"	7.22"	7.22"	7.22"	7.50"
OUTLET HOSE DIAMETER	3"	3"	3.5"	3.5"	3.5"	3.5"	4"	4"	4"	4"	4"	4"	4.5"	4.5"	4.5"
OUTLET I.D.	2.62"	2.62"	3.15"	3.15"	3.15"	3.15"	3.59"	3.59"	3.59"	3.59"	3.59"	3.59"	4"	4"	4"
MAX IMPELLER RPM	74,000	68,000	72,000	65,000	74,000	74,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000
INTERNAL STEP-UP	5.40:1	5.40:1	5.40:1	5.40:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	4.77:1	4.77:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	No	No
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OIL CAPACITY	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	4 oz	6 oz	6 oz	6 oz	6 oz

5" V-band flange discharge option available for 12"-13.5" head units

See Other Side for Street Supercharger Specs

INVENTED, ENGINEERED, MADE IN THE USA

04/21

FIND YOUR BOOST AT
PROCHARGER.COM

14801 W. 114th Terrace, Lenexa KS 66215 PH: (913) 338-2886 FX: (913) 338-2879

