

# STREET/STRIP

## PROCHARGER SUPERCHARGER SPECIFICATIONS

See Other Side for Race/Pro Supercharger Specs



|                                | A-1R   | B-1     | CS-1    | C-1     | C-2     | P600B   | P-1SC   | P-1SC-1 | P-1X    | P-1R    | D-1     | D-1SC   | D-1X    | F-1D    | F-1     | F-1A    | F-1A-91 | F-1A-94 |
|--------------------------------|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| <b>VOLUTE DIAMETER</b>         | 7"     | 7"      | 7"      | 7"      | 7"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      | 9"      |
| <b>MAX SUPERCHARGED HP</b>     | 150    | 250     | 550     | 675     | 725     | 775     | 825     | 825     | 950     | 1250    | 925     | 925     | 1075    | 1050    | 1050    | 1100    | 1200    | 1300    |
| <b>MOTOR BASE HP RANGE*</b>    | 50-95  | 60-150  | 150-325 | 150-325 | 175-375 | 200-500 | 200-500 | 200-450 | 300-500 | 300-500 | 300-500 | 300-500 | 300-550 | 300-500 | 300-500 | 300-500 | 300-500 | 300-550 |
| <b>MAX FLOW (CFM)</b>          | 450    | 600     | 900     | 1,000   | 1,000   | 1,150   | 1,200   | 1,200   | 1,275   | 1,600   | 1,400   | 1,400   | 1,500   | 1,500   | 1,525   | 1,575   | 1,600   | 1,625   |
| <b>MAX BOOST (PSI)</b>         | 15     | 20      | 24      | 24      | 24      | 24      | 30      | 32      | 32      | 36      | 32      | 32      | 32      | 34      | 38      | 38      | 38      | 38      |
| <b>INLET HOSE DIAMETER</b>     | 3"     | 3"      | 3.5"    | 3.5"    | 3.5"    | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 3.75"   | 4"      |
| <b>INDUCER DIAMETER</b>        | 2.28"  | 2.28"   | 2.66"   | 2.75"   | 3.14"   | 3.37"   | 3.37"   | 3.37"   | 3.57"   | 3.89"   | 3.37"   | 3.37"   | 3.57"   | 3.37"   | 3.57"   | 3.5"    | 3.57"   | 3.7"    |
| <b>EXDUCER DIAMETER</b>        | 3.2"   | 3.2"    | 3.7"    | 4.25"   | 4.25"   | 6.25"   | 6.25"   | 5.25"   | 5.56"   | 6.20"   | 6.25"   | 6.25"   | 6.20"   | 6.25"   | 6"      | 5.56"   | 5.56"   | 5.56"   |
| <b>OUTLET HOSE DIAMETER</b>    | 2"     | 2"      | 2.5"    | 2.5"    | 2.5"    | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      | 3"      |
| <b>OUTLET I.D.</b>             | 1.75"  | 1.75"   | 2.12"   | 2.12"   | 2.12"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   | 2.62"   |
| <b>MAX IMPELLER RPM</b>        | 75,000 | 110,000 | 80,000  | 80,000  | 80,000  | 60,000  | 62,000  | 65,000  | 65,000  | 65,000  | 65,000  | 62,000  | 65,000  | 65,000  | 70,000  | 74,000  | 74,000  | 74,000  |
| <b>INTERNAL STEP-UP</b>        | 4.11:1 | 4.95:1  | 8.30:1  | 4.70:1  | 4.70:1  | 3.05:1  | 4.10:1  | 4.10:1  | 4.10:1  | 4.10:1  | 4.44:1  | 4.10:1  | 4.10:1  | 5.40:1  | 5.40:1  | 5.40:1  | 5.40:1  | 5.40:1  |
| <b>REVERSE ROTATION OPTION</b> | Yes    | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     |
| <b>SELF CONTAINED</b>          | Yes    | Yes     | Yes     | Yes     | Yes     | No      | Yes     | Yes     | Yes     | Yes     | No      | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     | Yes     |
| <b>OIL CAPACITY</b>            | 2.5 oz | 2.5 oz  | 3.2 oz  | 2.5 oz  | 2.5 oz  | -       | 6 oz    | 6 oz    | 6 oz    | 6 oz    | -       | 6 oz    | 6 oz    | 4 oz    | 4 oz    | 4 oz    | 4 oz    | 4 oz    |

*See Other Side for F-Series Supercharger Specs*

913-338-2886 | SALES@PROCHARGER.COM | PROCHARGER.COM

07/26



**MADE IN THE USA**