

STREET/STRIP

PROCHARGER SUPERCHARGER SPECIFICATIONS

See Other Side for Race/Pro Supercharger Specs



	A-1R	B-1	CS-1	C-1	C-2	P600B	P-1SC	P-1SC-1	P-1X	P-1R	D-1	D-1SC	D-1X	F-1D	F-1	F-1A	F-1A-94
VOLUTE DIAMETER	7"	7"	7"	7"	7"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"	9"
MAX SUPERCHARGED HP	150	250	550	675	725	775	825	825	950	1200	925	925	1075	1050	1050	1100	1300
MOTOR BASE HP RANGE	50-95	60-150	150-325	150-325	175-375	200-500	200-500	200-450	300-500	300-500	300-500	300-500	300-550	300-500	300-500	300-500	300-550
MAX FLOW (CFM)	450	600	900	1,000	1,000	1,150	1,200	1,200	1,275	1,600	1,400	1,400	1,500	1,500	1,525	1,575	1,625
MAX BOOST (PSI)	15	20	24	24	24	24	30	32	32	36	32	32	32	34	38	38	38
INLET HOSE DIAMETER	3"	3"	3.5"	3.5"	3.5"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	4"
INDUCER DIAMETER	2.28"	2.28"	2.66"	2.75"	3.14"	3.37"	3.37"	3.37"	3.57"	3.89"	3.37"	3.37"	3.57"	3.37"	3.57"	3.5"	3.7"
EXDUCER DIAMETER	3.2"	3.2"	3.7"	4.25"	4.25"	6.25"	6.25"	5.25"	5.56"	6.20"	6.25"	6.25"	6.20"	6.25"	6"	5.56"	5.56"
OUTLET HOSE DIAMETER	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"
OUTLET I.D.	1.75"	1.75"	2.12"	2.12"	2.12"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"
MAX IMPELLER RPM	75,000	110,000	80,000	80,000	80,000	60,000	62,000	65,000	65,000	65,000	65,000	62,000	65,000	65,000	70,000	74,000	74,000
INTERNAL STEP-UP	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1	5.40:1	5.40:1	5.40:1	5.40:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes
OIL CAPACITY	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz	4 oz	4 oz	4 oz	4 oz

See Other Side for F-Series Supercharger Specs

913-338-2886 | SALES@PROCHARGER.COM | PROCHARGER.COM

08/26



RACE

PROCHARGER SUPERCHARGER SPECIFICATIONS

See Other Side for Street/Strip Supercharger Specs



	F-1R	F-1R-103	F-1X	F-2	F-3D-102	F-3D-106	F-3R-102	F-3R-112	F-3R-121	F-3R-130	F-3R-136	F-4R-136	F-4X-136	F-4X-140	F-4X-140-1	F-4X-146
VOLUTE DIAMETER	9.75"	9.75"	10.5"	10.5"	10.5"	10.5"	12"	12"	12"	12"	12"	12"	13.5"	14.5"	14.5"	14.5"
MAX SUPERCHARGED HP	1,250	1,500	1,550	1,450	1,500	1,800	1,600	2,100	2,400	2,700	3,000	3,000	3,200	3,700	4,000	4,500
MOTOR BASE HP RANGE	375-550	450-650	375-550	425-600	550-750	550-750	375-550	CALL	CALL	CALL	CALL	CALL	CALL	CALL	CALL	CALL
MAX FLOW (CFM)	1,700	1,900	2,000	2,100	1,900	2,200	2,000	2,300	3,100	3,600	4,000	4,000	4,200	4,500	4,700	5,200
MAX BOOST (PSI)	38	38	38	38	38	38	38	38	40	45	50	50	55	60	65	72
INLET HOSE DIAMETER	4.05"	4.25"	4.8"	4.6"	4.8"	4.8"	6"	5"	5.5"	5.75"	5.75"	5.75"	6"	6"	6"	6"
INDUCER DIAMETER	4"	4.25"	4.2"	4.5"	4"	4.2"	4"	4.4"	4.8"	5.12"	5.23"	5.23"	5.35"	5.37"	5.55"	5.75"
EXDUCER DIAMETER	6"	6"	6"	6.75"	6"	6"	6.75"	6.75"	6.75"	7.22"	7.22"	7.22"	7.22"	7.22"	7.22"	7.92"
OUTLET HOSE DIAMETER	3"	3.5"	3.5"	3.5"	3.5"	3.5"	4.5"	4"	4"	4"	4"	4"	4.5"	5"	5"	5"
OUTLET I.D.	2.62"	3.15"	3.15"	3.15"	3.15"	3.15"	3.59"	3.59"	3.59"	3.59"	3.59"	3.59"	4"	5"	5"	5"
MAX IMPELLER RPM	68,000	72,000	72,000	65,000	74,000	74,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	72,000	68,000
INTERNAL STEP-UP	5.40:1	5.40:1	5.40:1	5.40:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	5.63:1	4.7:1	4.7:1	4.7:1	4.7:1	4.7:1
REVERSE ROTATION OPTION	Yes	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	No	No	No	No	No
SELF CONTAINED	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OIL CAPACITY	4 oz	4 oz	4 oz	4 oz	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil	6 oz Race Oil

• F-1/F-2 superchargers are rated based upon high horsepower street engines. F-3 superchargers are rated based upon maximum effort race engines.

• The stated figures are not absolutes, and may actually be higher depending upon the specific application.

• Please refer to www.procharger.com for additional supercharger specifications

• Figures based on stated peak airflows; actual power levels may be higher in well prepared engines.

• Engine intake air temperature is the most relevant thermal measure (not SAE J1723) for a supercharger installed on a vehicle, especially when intercooled; SAE J1723 does not address the impact of engine dynamics, engine compartment heat transfer, intercooling or deficiencies caused by supercharger location.

913-338-2886 | SALES@PROCHARGER.COM | PROCHARGER.COM

08/26

